


# Airkewld 17" Smoothies

Something NEW for 2020, is the use of Smart Phone integrations by scanning QR codes with your phone's camera or a QR code app. Any time you see a  that tool is available on our [Amazon tool page](#). If a Video tutorial has been created for this product, you will find it [here](#). If you have a tech question, you can [text us here](#).

17" (2 Piece - No bolts showing) Smoothies are made up of a t-6061 billet aluminum center and a steel outer hoop. They are fastened together with a 16 bolts.

3/8" 12pt is the socket size for these bolts

Torque on ferry cap bolt is (31ft lbs)

Thread pitch on the ferry cap bolts is ( 3/8-16 )

Wolfsburg West hub cap clips are used and fastened with 10/32 stainless socket head cap screws.

All bolts and screws must have anti-seize applied to them.

Standard valve stems are utilized.

Acorn seat lug nuts are to be used.

Recommended balance is lug-centric.

Recommended tire sizes are p205-40r17 tires up front and p215-45r17 tires in the rear.

Any early hubcap from a 49-65 Beetle, 55-67 Bus or early 356 Porsche will work. Any aftermarket hub cap for those models will work but pick wisely because some caps are built with thinner steel or cheap chrome so inspect before purchasing.

The PRO's are always updating our install articles with tips, tools and videos that make the installs easier for all parties. If you have a tip or suggestions, please text or use What's App 1-623-518-3537 and let us know, we appreciate it.

## Tools you need



## Video Tutorials



## Tech Support

